

MSDS for: LN-604**Revised: 4-Jun-2004****SECTION 1:**

PRODUCT IDENTIFIER: LN-604 LATEX PROJECT & FOAM ADHESIVE
DATE OF PREPARATION: JUNE 4, 2004
PRODUCT USE: ADHESIVE

MANUFACTURED BY: MACCO ADHESIVES
925 EUCLID AVENUE
CLEVELAND, OHIO 44115, U.S.A.

ICI PAINTS (CANADA)
8200 KEELE STREET
CONCORD, ONTARIO L4K 2A5, CANADA

EMERGENCY AND MSDS TELEPHONE NUMBER: 1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND TOXICOLOGY DEPARTMENT
ICI PAINTS NORTH AMERICA

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT		WT.%
CHEMICAL NAME:	ACRYLIC RESIN	10-20
COMMON NAME:	ACRYLIC RESIN	
CAS NUMBER:	CONFIDENTIAL	
CHEMICAL NAME:	LIMESTONE	30-40
COMMON NAME:	LIMESTONE	
CAS NUMBER:	1317-65-3	
CHEMICAL NAME:	KAOLIN	5-10
COMMON NAME:	CLAY	
CAS NUMBER:	1332-58-7	
CHEMICAL NAME:	QUARTZ	0.1-1.0
COMMON NAME:	QUARTZ	
CAS NUMBER:	14808-60-7	
CHEMICAL NAME:	WATER	30-40
COMMON NAME:	WATER	
CAS NUMBER:	7732-18-5	
CHEMICAL NAME:	1,2-BENZENEDICARBOXYLIC ACID, BUTYL PHENYLMETHYL ESTER	1-5
COMMON NAME:	BUTYL BENZYL PHTHALATE	
CAS NUMBER:	85-68-7	

SECTION 3: HAZARDS IDENTIFICATION

HMIS CODE: *1-1-0-A

PRIMARY ROUTE(S) OF EXPOSURE: INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION

EFFECTS OF OVEREXPOSURE

INHALATION: IRRITATION OF RESPIRATORY TRACT. PROLONGED INHALATION MAY LEAD TO PNEUMOCONIOSIS.

SKIN CONTACT: IRRITATION OF SKIN.

EYE CONTACT: IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE TEARING OF EYES, REDNESS OF EYES.

INGESTION: INGESTION MAY CAUSE MOUTH AND THROAT IRRITATION, NAUSEA, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

EYE, SKIN, RESPIRATORY DISORDERS, LUNG DISORDERS, RESPIRATORY DISORDERS.

SECTION 4: FIRST-AID MEASURES

INHALATION: REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING. GET EMERGENCY MEDICAL ATTENTION. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY. REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING, HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.

SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

INGESTION: IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA): ABOVE 200F/93C LOWER EXPLOSIVE LIMIT: NOT AVAILABLE
UPPER EXPLOSIVE LIMIT: NOT AVAILABLE

FIRE EXTINGUISHING MEDIA: DRY CHEMICAL OR FOAM, WATER FOG, CARBON DIOXIDE

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE. FIRE FIGHTING PROCEDURES WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS:

CARBON MONOXIDE, CARBON DIOXIDE, ACRYLIC MONOMERS,
OXIDES OF CALCIUM

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. PLACE COLLECTED MATERIAL IN PROPER CONTAINER.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: STORE BELOW 100F (38C). KEEP FROM FREEZING.

OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME: LIMESTONE
CAS NUMBER: 1317-65-3
ACGIH(TWA): 10 MG/M3 OSHA(TWA): 5 MG/M3

COMMON NAME: CLAY
CAS NUMBER: 1332-58-7
ACGIH(TWA): 2 MG/M3 OSHA(TWA): 5 MG/M3

COMMON NAME: QUARTZ
CAS NUMBER: 14808-60-7
ACGIH(TWA): 0.05MG/M3 OSHA(TWA): 0.1 MG/M3

COMMON NAME: BUTYL BENZYL PHTHALATE
CAS NUMBER: 85-68-7
ACGIH(TWA): 5 MG/M3 OSHA(TWA): 5 MG/M3

RESPIRATORY PROTECTION

WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE WITH OSHA STANDARD 29 CFR 1910.134.

VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES, IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.449
BOILING RANGE (F/C):	212-698/100-370	WEIGHT PER GALLON:	12.07/ 14.50 IMP
APPEARANCE:	WHITE	%VOLATILE BY VOLUME:	55.67
PHYSICAL STATE:	PASTE	HMIS CODE:	*1-1-0-A
PH:	9.00	SOLUBILITY IN WATER:	Y

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS:	STABLE (SEE SECTION 5 FIRE FIGHTING MEASURES)
MATERIALS TO AVOID:	ACIDS, STYRENE MONOMER
CONDITIONS TO AVOID:	ELEVATED TEMPERATURES, FREEZING
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME:	LIMESTONE			
CAS NUMBER:	1317-65-3			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:	6450.00 MG/KG ORL RAT			

COMMON NAME:	CLAY			
CAS NUMBER:	1332-58-7			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO

COMMON NAME:	QUARTZ			
CAS NUMBER:	14808-60-7			
CARCINOGENICITY LISTED BY:	NTP YES	IARC YES 1	OSHA NO	ACGIH NO

COMMON NAME:	BUTYL BENZYL PHTHALATE			
CAS NUMBER:	85-68-7			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:	2330.00 MG/KG ORL RAT			
LD50:	6700.00 MG/KG SKN RAT			

SUPPLEMENTAL HEALTH INFORMATION

NO ADDITIONAL EFFECTS ARE ANTICIPATED.

CARCINOGENICITY: CONTAINS CRYSTALLINE SILICA WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED CRYSTALLINE SILICA AS CARCINOGENIC TO HUMANS (GROUP 1). CRYSTALLINE SILICA IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE. THE NATIONAL TOXICOLOGY PROGRAM (NTP) HAS CLASSIFIED CRYSTALLINE SILICA AS A KNOWN HUMAN CARCINOGEN.

REPRODUCTIVE EFFECTS: NO REPRODUCTIVE EFFECTS ARE ANTICIPATED

MUTAGENICITY: NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY: NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY ICI PAINTS ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT: ADHESIVE
IMDG: NOT AVAILABLE
IATA: NOT AVAILABLE
TDG: NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

	SARA 302	SARA 313	CERCLA 302.4	HAZ AIR POLLUTANT	MARINE POLTNT
CAS NUMBER: 85-68-7	NO	NO	YES	NO	
COMMON NAME: BUTYL BENZYL PHTHALATE					

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH ICI PAINTS BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. ICI PAINTS SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL. COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.